

Closed containers may burst if exposed to extreme heat or fire.
SPECIAL FIRE FIGHTING PROCEDURES:
Cool exposed containers with water. Use self-contained breathing apparatus.

SECTION V HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - ACUTE:
Inhalation - Irritation of the respiratory tract.
Contact - Causes eye burns.
Contact - Causes Skin burns.
Ingestion of large amounts could cause serious injury.
EFFECTS OF OVEREXPOSURE - CHRONIC:
None expected when used in accordance with Safe Handling and Use Information (Section VIII)
MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:
None expected when used in accordance with Safe Handling and Use Information (Section VIII).
PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION
EMERGENCY AND FIRST AID PROCEDURES :
Inhalation - Remove to fresh air. Get medical help for any breathing difficulty.
Eye Contact - Flush thoroughly with water. Call physician.
Skin Contact - Wash with soap and water. Call physician
Ingestion - Drink 1 or 2 glasses of water to dilute.
DO NOT induce vomiting. Call physician.

SECTION VI REACTIVITY DATA

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR
CONDITIONS TO AVOID: Elevated temperatures
HAZARDOUS DECOMPOSITION PRODUCTS:
Carbon monoxide, carbon dioxide, sodium oxides, ammonia, polyacrylates and acrylic acid.
May produce Hydrogen gas on contact with aluminum, zinc or magnesium alloys.
INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing Agents, acids, alkalies, organic halogens, ammonia, organic amines reducing sugars and nitromethane.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Absorb spillage with inert material and dispose of in accordance with applicable regulations.
WASTE DISPOSAL METHOD:
Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

SECTION VIII SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:
Wear a properly fitted gas / vapor respirator with mist/dust filter approved by NIOSH during spray application.
VENTILATION:
Adequate to maintain working atmosphere below T.L.V. and L.E.L.
(See Sect. II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.
SKIN PROTECTION: Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

EYE PROTECTION : Splash goggles or safety glasses with side shields.
OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.
HYGIENIC PRACTICES:
Remove and discard clothing. Wash hands before eating, smoking
or using the washroom.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not throw or drop containers.

OTHER PRECAUTIONS :

Avoid contact with eyes and prolonged contact with skin or breathing of
spray mist or sanding dust.

Close container after each use. Keep out of reach of children. Do not
take internally.

TRANSPORTATION: DOT Class 8, "Corrosive"

SECTION XX

HMIS (Hazardous Materials Identification System)(R) NPCA
HMIS is a recognized workplace Hazard Communications System as required by
OSHA (29 CFR 1910.1200). Information on establishing a compliant hazardous
communication program using HMIS is available from:

American Labelmark Co., Inc., Labelmaster Division
5724 N. Pulaski Rd., Chicago, IL 60646
1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings;
the contractor/employer has ultimate responsibility for HMIS rating where
this system is used.

PERSONAL PROTECTION: This code is left blank on Benjamin Moore & Co. MSDS's
as it depends on application technique and the workplace ventilation.
Please read Sections II through IX of this MSDS before deciding on
appropriate protective equipment and beginning work. There are codes
available for this section which can be obtained from Labelmaster.

Note: There are no SARA reportable materials in this product.

DISCLAIMER

The information contained herein is presented in good faith and believed
to be accurate as of the effective date shown above. This information is
furnished without warranty of any kind. Employers should use this
information only as a supplement to other information gathered by them and
must make independent determination of suitability and completeness of
information from all sources to assure proper use of these materials and
the safety and health of employees. Any use of this data and information
must be determined by the user to be in accordance with applicable federal,
state and local laws and regulations.

WARNING: If you scrape, sand, or remove old paint, you may release lead
dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS,
SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO
AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure.
Clean up carefully with a HEPA vacuum and a wet mop. Before you start,
find out how to protect yourself and your family by contacting the National
Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.