



Moore's® House & Trim Paint 130

Features

- Dries to a beautiful protective gloss finish
- Offers lasting durability
- Excellent leveling and hiding qualities
- Exhibits controlled chalking and resists rundown on adjacent surfaces
- Flows on smoothly and freely, covering most surfaces in good repaint condition in one coat
- Specially formulated to resist mildew growth on the paint film
- Ultra hide formula

General Description

A premium quality, long-oil alkyd house paint, that provides a beautiful gloss finish and superior coverage.

Recommended For:

Residential or commercial applications where a superior quality traditional high gloss oil finish is desired.

For exterior use on primed or previously painted wood siding, doors, sash, or trim; aluminum or hard-board siding; properly primed or previously painted galvanized metal or ferrous surfaces.

Limitations:

- Do not apply when air and surface temperatures are below 50° F (10° C).

Product Information

Colors: —Standard:

Brilliant White

—Tint Bases:

Not available

—Special Colors:

Contact your Benjamin Moore & Co. representative

Certification:

Formulated without lead or mercury.
Formulated with non-photochemically reactive solvents.

Federal Specifications Generic Equivalents:

TT-P-102-E
TT-P-81-E

Technical Assistance

Available through your local authorized independent BENJAMIN MOORE® retailer. For the location of the retailer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.

Technical Data

Brilliant White

Vehicle Type	Alkyd
Pigment Type [◇]	Titanium Dioxide
Volume Solids [◇]	58%
Theoretical Coverage At Recommended Film Thickness	450 – 500 Sq. Ft.
<i>Depending on surface texture and porosity. Be sure to estimate the right amount of product for the job. This will ensure color uniformity and minimize the disposal of excess paint.</i>	
Recommended Film Thickness – Wet – Dry	3.4 mils 2.0 mils
Dry Time @ 77° F — Dry To Touch (25° C) @ 50% RH — To Recoat – To Hard Dry	4 Hours 24 Hours Overnight
Dries By	Evaporation, Oxidation
Viscosity [◇]	93 ± 2 KU
Flash Point (Seta)	Combustible
60° Specular Gloss	High Gloss
Surface Temperature at application – Min. – Max.	50° F 90° F
Thin With	Do Not Thin
Clean Up Thinner	Mineral Spirits
Weight Per Gallon [◇]	11.0 lbs.
Storage Temperature – Min. – Max.	40° F 90° F
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 380 Grams/Liter.**</i>	

TDS130A

** Contact Benjamin Moore & Co. for actual levels, which may or may not be substantially less than stated.
[◇] Values given are for color shown; other colors may vary.

Moore's® House & Trim Paint (130)

Surface Preparation

Surfaces must be clean and free of grease, wax, and mildew. Remove excessive chalk and loose or scaling paint. If previously coated with cement-base water paints, clean by sandblasting. Glossy surfaces must be dulled. **Unweathered areas such as eaves, ceilings, and overhangs should be washed with a detergent solution and/or rinsed with a strong stream of water from a garden hose to remove contaminants that can interfere with proper adhesion.** Mildew must be removed by application of BENJAMIN MOORE® CLEAN (318). **Caution:** Use rubber gloves, work goggles, and protective clothing. For metal surfaces, remove rust. Wipe down with paint thinner to remove surface oils.

When applying on previously coated cedar or redwood, test an area for tannic acid bleeding. It will be particularly noticeable when applying lighter colored films. Should bleeding occur, prime entire surface with BENJAMIN MOORE FRESH START® MOORWHITE® Penetrating Alkyd Primer (100) before application of finish.

Poured and precast concrete must be allowed to cure for 60 – 90 days; block construction should be allowed to cure for 30 – 60 days. A common exterior paint failure on masonry construction is peeling and scaling, often caused by painting over heavy chalk deposits. The most practical and efficient way to remove this substance is with high pressure spray equipment. Multiple coats of paint that are in advanced state of deterioration or prior applications of cement based coatings must be removed to a sound substrate. Sandblasting or using a mechanical grinder are effective means of preparation. All surfaces must be thoroughly brushed with stiff fibre bristles to remove loose particles.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

For best hiding results, tint the primer to the approximate shade of the finish coat. **Special Note:** Certain custom colors require a Deep Base Primer tinted to a special prescription formula to achieve the desired color. Consult your retailer.

Note: To minimize tannin staining from cedar or redwood, spot-prime butt ends, joints or scraped areas in addition to overall priming. Spot-prime stained areas on previously painted woods before priming.

Benjamin Moore & Co. offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease, crayon markings, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem. Your BENJAMIN MOORE® retailer can recommend the right problem-solving primer for your special needs.

Wood, New (Including Shakes and Shingles):

Primer: BENJAMIN MOORE FRESH START® MOORWHITE® Penetrating Alkyd Primer (100)
Finish: 1 or 2 coats MOORE'S® House Paint

Wood, Repaint (Including Shakes and Shingles):

Primer: Prime or spot prime as needed with BENJAMIN MOORE FRESH START® MOORWHITE® Penetrating Alkyd Primer (100)
Finish: 1 or 2 coats MOORE'S® House Paint

Hardboard Siding, Bare or Factory Primed:

Primer: BENJAMIN MOORE FRESH START® MOORWHITE® Penetrating Alkyd Primer (100)
Finish: 1 or 2 coats MOORE'S® House Paint

Hardboard Siding, Repaint:

Primer: Prime or spot prime as needed with BENJAMIN MOORE FRESH START® MOORWHITE® Penetrating Alkyd Primer (100)
Finish: 1 or 2 coats MOORE'S® House Paint

Masonry, New and Unpainted (Including Unglazed Brick):

Priming Rough or Pitted Masonry:
Primer: MOORCRAFT SUPER CRAFT® Latex Block Filler (285)
Finish: 1 or 2 coats MOORE'S® House Paint
Priming Smooth Poured or Precast Concrete:
Primer: BENJAMIN MOORE FRESH START® 100% Acrylic Latex Primer (023)
Finish: 1 or 2 coats MOORE'S® House Paint

Masonry, Weathered and Unpainted (Including Unglazed Brick):

Remove any loose, sandy masonry by dry brushing.
Primer: MOORE'S® Alkyd Masonry Sealer — White (C077 01) or Clear (C077 00) or MOORE'S® Acrylic Masonry Sealer (066)
Finish: 1 or 2 coats MOORE'S® House Paint

Masonry, Repaint (Including Unglazed Brick):

Primer: Prime or spot prime as needed with BENJAMIN MOORE FRESH START® Acrylic (023). If heavy chalk was present prior to washing, prime with BENJAMIN MOORE® (066) Acrylic or (C077) Alkyd Masonry Sealers
Finish: 1 or 2 coats MOORE'S® House Paint

Ferrous Metal:

Primer: IRONCLAD® Alkyd Low Lustre Metal and Wood Enamel (C163)
Finish: 1 or 2 coats MOORE'S® House Paint

Application

Stir thoroughly before and occasionally during use. Apply 1 or 2 full even coats by brush, roller or spray gun.

Do not add other paints or solvents.

Spray, Airless: Fluid Pressure — 1,500 to 2,000 PSI;
Airless Tip — .015 to .017 Orifice; Filter — 100 mesh

Thinning/Cleanup

Do not thin.

Clean brushes and equipment with mineral spirits.

USE COMPLETELY OR DISPOSE OR PROPERLY. This product contains organic solvents which may cause adverse effects to the environment if handled improperly. Save unused product for touch-up purposes or a household hazardous waste collection program. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary, consult your sanitation department or state-designated environmental agency on disposal options.**

DANGER – RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

Environmental, Health & Safety Information

WARNING! COMBUSTIBLE LIQUID AND VAPOR! VAPOR HARMFUL. Contains Stoddard Solvent, Xylene and Crystalline Silica CAUSES EYE, SKIN, NOSE, AND THROAT IRRITATION.

NOTICE: Repeated and prolonged exposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are signs that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **Crystalline silica** can cause cancer when in the respirable form (spray mist or sanding dust).

Keep away from heat and flame. **Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves. To avoid breathing vapors or spray mist, open window and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear a properly fitted vapor/particulate respirator approved by NIOSH for use with paints or leave the area. In all cases follow respirator manufacturer's directions for respirator use. Close container after each use.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician; for skin, wash thoroughly with soap and water. In case of ingestion, DO NOT INDUCE VOMITING. Get medical help immediately.

IN CASE OF: FIRE – Use foam, CO₂, dry chemical, or water fog.

SPILL – Absorb with inert material and dispose of as specified under **Thinning/Cleanup**.

KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet for additional health and safety information.

